

SAFETY DATA SHEET

According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS) Revision Date Feb 01, 2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name CAS-No. Product code ACETIC ACID GLACIAL 64-19-7 AR1002, BP1002, EP1002, GP1002, LC1002, RP1002, SM1002, VL1002

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses Chemical for analysis and production.

1.3 Details of the supplier of the safety data sheet

| Company | RCI LABSCAN LIMITED. |
|------------------|---|
| | 24 Rama 1 Road, Pathumwan, Bangkok 10330 Thailand |
| Telephone number | (662) 613-7911-4 |
| Fax number | (662) 613-7915 |
| | |

1.4 Emergency Telephone Number

Emergency phone (662) 613-7911-4

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 Flammable liquid and vapour (Category 3), H226 Skin corrosion (Category 1A), H314 For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

| | Flammable | R10 | |
|-----------|---------------------------|---------------------------|---------------|
| С | Corrosive | R35 | |
| Ear tha f | ull taxt of the P phrases | montioned in this Section | and Section 1 |

For the full text of the R-phrases mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

| Hazard statement(s) | |
|---------------------|--|
| H226 | Flammable liquid and vapour. |
| H314 | Causes severe skin burns and eye damage. |

| Precautionary statement(s) | |
|----------------------------|---|
| P210 | Keep away from heat/sparks/open flames/hot surfaces No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/Bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting equipment. |
| P242 | Use only non-sparking tools. |

| P243 | Take precautionary measures against static discharge. |
|--------------------|--|
| P260 | Do not breathe vapours/ spray. |
| P264 | Wash hand thoroughly after handling. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301 + P330 + P331 | IF SWALLOWED: rinse mouth. Do NOT induce vomiting. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304 + P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER or doctor/physician. |
| P363 | Wash contaminated clothing before reuse. |
| P370 + P378 | In case of fire: Use carbon dioxide, dry chemical, foam or water spray for extinction. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| 2.3 Other hazards | None |

SECTION 3: Composition/information on ingredients

3.1 Substances

| Synonyms | Acetic acid, Ethanoic acid, Ethylic acid, Methane carboxylic acid, Vinegar acid. | | | | ar acid. |
|----------|--|-------------|---------|------------------|----------|
| CAS-No | EC-No | EC-Index-No | Formula | Molecular Weight | Weight |

| CAS-No | EC-No | EC-Index-No | Formula | Molecular Weight | Weight % |
|---------|-----------|--------------|---------|------------------|----------|
| 64-19-7 | 200-580-7 | 607-002-00-6 | CH₃COOH | 60.05 g/mol | >99 |

Hazardous ingredients according to Regulation (EC) No 1272/2008

| C | omponent | Concentration | Classification |
|-------------|----------------|---------------|-------------------------------------|
| Acetic acid | | | |
| CAS-No | 64-19-7 | >99% | Flammable liquid (Category 3), H226 |
| EC-No | 200-580-7 | | Skin corrosion (Category 1A), H314 |
| EC-Index-N | o 607-002-00-6 | | |

Hazardous ingredients according to Directive 1999/45/EC

| C | component | Concentration | Classification |
|-------------|-----------------|---------------|-------------------|
| Acetic acid | k | | |
| CAS-No | 64-19-7 | >99% | Flammable, R10 |
| EC-No | 200-580-7 | | C, Corrosive, R35 |
| EC-Index-N | lo 607-002-00-6 | | |

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

| General advice | Show this safety data sheet to the doctor in attendance. |
|----------------|---|
| Inhalation | Move to fresh air in case of accidental inhalation of vapors. Keep patient warm. In case of |
| | shortness of breath, give oxygen. Apply artificial respiration only if patient is not breathing |
| | or under medical supervision. No artificial aspiration mouth to mouth or mouth to nose. |
| | Use suitable instruments/apparatus. |

| Skin contact | Remove contaminated clothing and wash affected skin with soap and water. Dab with |
|--------------|---|
| | polyethylene glycol 400. Obtain medical attention. If signs of poisoning appear, treat as for |
| | inhalation. Wash contaminated clothing before reuse. Contaminated combustible material, |
| | e.g. clothing ignites more readily and burns fiercely. |
| Eye contact | If the substance has got into the eyes, immediately wash out with plenty of water at least |
| | 15 minutes. Obtain medical attention. |
| Ingestion | Rinse mouth. Do not induce vomiting. Keep patient warm. In case of shortness of breath, |
| | give oxygen. Apply artificial respiration only if patient is not breathing or under medical |
| | supervision. No artificial aspiration mouth to mouth or mouth to nose. Use suitable |
| | instruments/apparatus. Obtain medical attention. Never give anything by mouth to an |
| | unconscious person. |

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2.2 and section 11

4.3 Indication of any immediate medical attention and special treatment needed

After swallowing: make victim drink water (two glasses at the most), avoid vomiting (risk of perforation). Immediately call in physician. Do not attempt to neutralize.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguish with carbon dioxide, dry chemical, foam or water spray. In the event of fire, cool tanks with water spray.

5.2 Special hazards arising from the substance or mixture

Combustible. Vapors heavier than air. Forms explosive mixtures with air at ambient temperatures. Development of hazardous combustion gases or vapors possible in the event of fire. The following may develop in event of fire: Acetic acid vapors.

5.3 Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

5.4 Further information

Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Do not breathe vapors or spray mist. Remove all sources of ignition. Wear a positive-pressure supplied-air respirator, flame retardant antistatic protective clothing. Shut off leaks if without risk. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Contain or absorb leaking liquid with sand or earth, consults an expert. Prevent liquid entering sewers, basements and workpits. If substance has entered a water course or sewer or contaminated soil, advise police.

6.3 Methods and materials for containment and cleaning up

Spillage: May react with combustible substances creating fire or explosion hazard and formation of toxic fumes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Soak up with inert absorbent material (e.g. sand, silica gel). Prevent liquid entering sewers, basements and workpits; vapor may create explosive atmosphere. Transfer to covered steel drums. Dispose of promptly.

6.4 Reference to other sections

For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities

Keep tightly closed at room temperature in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep out of direct sunlight and away from incompatible materials. Store in original container. Electrical equipment should be protected to the appropriate standard. Requirements for containers, no metal containers.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

| Application Area | Health Effects | Exposure | Value |
|------------------|-------------------------|------------|----------|
| Worker | Acute Local effects | Inhalation | 25 mg/m³ |
| Worker | Long-term Local effects | Inhalation | 25 mg/m³ |
| Consumer | Acute Local effects | Inhalation | 25 mg/m³ |
| Consumer | Long-term Local effects | Inhalation | 25 mg/m³ |

Predicted No Effect Concentration (PNEC)

| Compartment | Value |
|------------------------------|-------------|
| Fresh water | 3.058 mg/l |
| Fresh water sediment | 11.36 mg/kg |
| Marine water | 0.3058 mg/l |
| Marine sediment | 1.136 mg/kg |
| Aquatic intermittent release | 30.58 mg/l |
| Sewage treatment plant | 85 mg/l |

8.2 Exposure controls

Appropriate engineering controls

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Ventilation hoods and fans required when working with organic solvents or in hot melt applications.

Individual protection measures (Personal protective equipment, PPE)

Eye/face protection

Goggles giving complete protection to eyes.

Skin protection

Chemical resistant apron / flame retardant antistatic protective clothing, heavy duty work shoes. Handle with gloves

- Full contact wears gloves from butyl rubber material.
- Splash contact wears gloves from natural latex material.

The select protective gloves have to satisfy the specifications of EU Directive 89/686 EEC and standard EN 374 derived from it.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Required when vapor/aerosols are

generated filter E-(P2) (EN 141 or EN 14387).

Environmental exposure controls

Prevent liquid entering sewers, basements and workpits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Appearance: From | Liquid |
|---|--|
| : Color | Colorless |
| Odour | Pungent |
| Odour Threshold | Not Available |
| рН | 2.5 at 50g/l (H₂O) at 20⁰C |
| Melting point/range | 17°C |
| Boiling point/range | 118°C |
| Flash point | 39 °C (closed cup) |
| Evaporation rate | Not Available |
| Flammability (solid, gas) | Not Available |
| | |
| Explosion limits: lower | 4 %(V) |
| upper | 19.9 %(V) |
| Vapor Pressure | 15.4 hPa at 20°C |
| Relative Vapor Density | 2.07 |
| Density | 1.05 g/ml at 20°C |
| Water solubility | Soluble at 20°C |
| Partition coefficient (n-octanol/water) | log Pow: -0.17 |
| Auto-Ignition temperature | 485 °C |
| Decomposition Temperature | Not Available |
| Viscosity | 1.22 mPa.s at 25°C |
| Explosive properties | Not Explosive |
| Oxidizing properties | The substance or mixture is not classified as oxidizing. |
| | |

SECTION 10: Stability and reactivity

10.1 Reactivity

In flammable. Incompatible with various metals. Explosible with air in a vaporous/gaseous state.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion in contact with hydrogen peroxide, chromium (VI)-oxide, potassium permanganate, sodium peroxide, perchloric acid, phosphorus trichloride.

The substance polymerize in contact with acetaldehyde.

The substance can react dangerously with alcohols, strong oxidizing agents, strong lyes, alkali hydroxide, strong acids, nitric acid, 2-aminoethanol, ammonium nitrate (heat), bromine pentafluoride, chlorosulphuric acid, dichromate-sulfuric acid, diaminoethane, acetic anhydride, ethylene glycol, potassium-tert. Butoxide, oleum

10.4 Conditions to avoid

Strong heating, temperature <0 °C

10.5 Incompatible materials

Anhydrides/water, aldehydes, alcohols, halogen-halogen compounds, oxidizing agent, chromium(VI)-oxide, potassium permanganate, peroxide compounds, perchloric acid, chromosulfuric acid, metal (iron, zinc, magnesium are generation of hydrogen), alkali hydroxides, nonmetallic halides, ethanolamine.

Incompatible with various metals

10.6 Hazardous decomposition products

Acetic acid vapors, carbon monoxides, carbon dioxides (Hazardous decomposition products from under fire condition).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD₅₀ (oral, rat): 3310 mg/kg LC₅₀ (inhalation, rat): 11.4 mg/l/4 h LD₅₀ (dermal, rabbit): 1060 mg/kg

Acute oral toxicity

Burns in oesophagus and stomach. Gastric spasms, bloody vomiting, dyspnoea. Risk of perforation in the oesophagus and stomach. Pulmonary failure possible after aspiration of vomit. Shock, cardiovascular failure, acidosis, Damage of kidneys.

Acute inhalation toxicity

Irritation symptoms in the respiratory tract. Pneumonia bronchitis. Inhalation may lead to the formation of oedemas in the respiratory tract.

Skin corrosion/irritation Burns

Serious eye damage/eye irritation Burns of mucous membranes. Risk of blindness and corneal clouding.

Respiratory or skin sensitization Not Available

Germ cell mutagenicity Bacterial mutagenicity; Salmonella typhimurium is negative.

Carcinogenicity

Not Available

Reproductive toxicity Not Available

Teratogenicity No teratogenic effect in animal experiments.

Specific target organ toxicity (STOT) - single exposure

Not Available

Specific target organ toxicity (STOT) - repeated exposure Not Available

Aspiration hazard Not Available

Further information

Systemic effects: gastric spasms, bloody vomiting, dyspnea, perforation in the oesophagus and stomach, shock, cardiovascular failure, acidosis. Damage of kidneys.

SECTION 12: Ecological information

12.1 Toxicity

| Toxicity to fish | LC ₅₀ L. macrochirus: 75 mg/l/96h |
|--|--|
| Toxicity to daphnia and other aquatic invertebrates | EC ₅₀ Daphnia magna: 47 mg/l /24h |
| Toxicity to algae | IC₅ Sc.quadricauda: 4000 mg/l/16h |
| Toxicity to bacteria | EC₅ Ps. Putida: 2850 mg/l /16h |
| | EC ₅ Protozoa: E.sulcatum: 78 mg/l/72 h |

12.2 Persistence and degradability

Biodegradability99%/30 d, Readily biodegradable.Biochemical Oxygen Demand (BOD)880 mg/g/5d.

12.3 Bioaccumulative potential

Partition coefficient (n-octanol/water)

log Pow: -0.17 No bioaccumulation is to be expected (log P o/w <1)

12.4 Mobility in soil

Not Available

12.5 Other adverse effects

Biological effects; Harmful effect on aquatic organisms. Harmful effect due to pH shift. Caustic even in diluted form.

Do not allow to enter waters, waste water or soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

There are no uniform EC Regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding law and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste or burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Contaminated packaging

Disposal in compliance with official regulations. Handle contaminated packaging as hazardous waste in the same way of the substance itself. If not officially specified differently, non-contaminated packaging may be treated like household waste or recycled.

SECTION 14: Transport information

Land Transport (ADR/RID)

| UN Number | 2789 |
|------------------------------|---------------------|
| UN proper shipping name | ACETIC ACID GLACIAL |
| Transport hazard class(es) | 8 (3) |
| Packaging group | II |
| Environmental hazards | No |
| Special precautions for user | Yes |
| Sea transport (IMDG) | |
| UN Number | 2789 |
| UN proper shipping name | ACETIC ACID GLACIAL |
| Transport hazard class(es) | 8 (3) |
| | |

| Packaging group | II |
|------------------------------|---------------------|
| Marine pollutant | No |
| Special precautions for user | Yes |
| EmS | F-E S-C |
| Air transport (IATA) | |
| UN Number | 2789 |
| UN proper shipping name | ACETIC ACID GLACIAL |
| Transport hazard class(es) | 8 (3) |
| Packaging group | II |
| Environmental hazards | No |
| Special precautions for user | No |
| | |

River transport (AND/ADNR)

(Not examined)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Not Available

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

| H226 | Flammable liquid and vapour. |
|------|------------------------------|
|------|------------------------------|

H314 Causes severe skin burns and eye damage.

Full text of R-phrases referred to under sections 2 and 3

| С | Corrosive |
|-----|----------------------|
| R10 | Flammable |
| R35 | Causes severe burns. |

Recommended restrictions

Take notice of labels and safety data sheets for the working. Chemicals Take necessary action to avoid static electricity discharge.

Reference

Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

Labelling according to EC Directives 67/548 EEC and Regulation (EC) No 1272/2008.

Transportation information according to Recommendations on the Transport of Dangerous Goods, Model Regulations. Twelfth revised edition. United Nations.

Institute for Occupational Safety and Health of the German Social Accident Insurance in Sankt Augustin/Germany, Source: IFA for Databases on hazardous substances (GESTIS).

Further information

Contact to RCI Labscan Limited.

Revision Date 01/02/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.